

## PRODUCT SPECIFICATION

### Micro-cement - Medium - Bi-Component.

#### DESCRIPTION:

Micro-Cement Medium is a coating that can be applied to any hard surfaces such as walls, floors, both indoors and out. This cement and medium quartz-based layer are at most 2-3mm thick.

#### USES:

- On existing tiles and old smooth concrete screeds
- Existing floors where carpet has been removed
- Plastered walls and ceilings
- Internal/external walls and floors
- Bathrooms and kitchens
- Worktops
- Stairwells and steps

#### IDENTIFICATION FEATURES:

- Micro-Cement Powder.
- Liquid resin Concentrate.

#### PERFORMANCE CHARACTERISTICS:

- Can be applied over other linings such as ceramic, porcelain, marble, mosaics, tiles, concrete and plaster.
- Low thickness allows for quick improvement of an existing concrete.
- Suitable for under-floor heating.
- Easy to clean.
- Highly resistant to UV Rays.
- Can be applied to bathrooms, kitchens, stairwells, facades, walls and any room in the house.
- Allows for seamless finish on floors and walls (no need for expansion joints).
- 

- Allows for commercial renovation without going into heavy construction work.
- Low maintenance, and can therefore be used to replace traditional flooring.

#### APPLICATION:

With a trowel or spatula.

#### PREPARING THE MIXTURE:

Mix the Powder with the resin and 6 liters of clean water the addition of the powder must be gradual and must always take place with mechanical mixing using a drill three minutes or until the components have been mixed completely.

Lifespan of the mixture: approx. 240 minutes.

The mixture obtained must not have lumps, portions of unmixed components, impurities.

#### TOOLS CLEANING:

With Water, immediately after use.

#### Coverage

Micro-Cement Medium: 0.5 - 0.6 kg/m<sup>2</sup>

Micro-cement Fino: 0.3 - 0.4 kg/m<sup>2</sup>, in one layer, on the basis of the type of intervention and the status of the substrate.

It is good practice to check the effective coverage via a preliminary test on the specific substrate.

#### COLORS:

White.

#### PACKAGES:

20 Kg Drum of powder pack.

1Ltr. Liquid Resin Concentrate.

The packaged product is guaranteed for 24 months, if stored in the original sealed package and at temperatures between +5°C and +35°C.

## SHELF LIFE