

PRODUCT SPECIFICATION

Micro-cement - W - Paste Bi-Component.

DESCRIPTION:

Micro-cement -W- Paste is a mineral plaster coat for the decoration of the vertical surfaces in prestigious places.

USES:

Top quality indoor decoration of highly valuable interiors in compliance with current trends in fashion and architecture.

IDENTIFICATION FEATURES:

Product in paste.
3.6 Kg of powder.
1Ltr of Concentrated Resin.

PERFORMANCE CHARACTERISTICS:

Thanks to its special formulation it allows to create a compact seamless surface.

APPLICATION

With a trowel or spatula.

PREPARING THE MIXTURE

Mix the three components together, the addition of the powder must be gradual and must always take place with mechanical mixing using a drill three minutes or until the components have been mixed completely. Lifespan of the mixture: approx. 240 minutes.

The mixture obtained must not have lumps, portions of unmixed components, impurities.

PRECAUTIONS:

Do not expose the products to direct heat sources or temperatures below +5°C for long periods of time. If the products are stocked at temperature of approx. +5°C, before use it is recommended to take them to a place with

SHELF LIFE

The packaged product is guaranteed for 24 months, if stored in the original sealed package and at temperatures between +5°C and +35°C.

suitable temperature, in a way to condition them to a temperature of use no lower than +10°C. Do not heat the products using a direct heat source, flame, hot body or similar. It is recommended to finish the job using the same production

batch. If different batches are used, we advise mixing the different batches together in order to avoid slight color differences.

The application of the "The Micro-Cement System" outdoors, means light colors must be selected and outdoor-resistant colorants must be used.

After application, the surfaces must be protected from rain and humidity until they are completely dry.

Exposure of the surface, which is not completely dry, to atmospheric agents, can generate the appearance of stains or irreversible bleaching phenomenon.

For correct use of the materials mentioned, dilution and application, read the relative technical data sheet carefully.

Correct use of individual protection equipment is recommended during all preparation of the substrate, products and application of the same.

TOOLS CLEANING:

With Water, immediately after use.

Coverage

Micro-cement Fine: 0.5 -0.7 kg/m², in the one layer, on the basis of the type of intervention and the status of the substrate. It is good practice to check the effective coverage via a preliminary test on the specific substrate.

COLORS:

White.

PACKAGES:

18 Kg Drum
3.6kg of powder pack.
1Ltr of Concentrated Resin.